



**CLEVER FILTRATION**

## The Cross Phoenix Filter

The flexible, adaptable and reliable filtration solution for the demands of today's industries, including:

- Water and effluent treatment
- Cooling towers and heating systems
- Machine shop coolants
- Food, drinks and pharmaceuticals
- Recycling and environmental management



## The Phoenix Filter Range



### Standard Features

'Zero Gravity' Coil Filtration:  
10-400 micron absolute filtration range  
Automatic backwashing  
No interruption to system flow  
No redundancy or bypass requirement

- Cyclonic 'Turbo' flow path, minimises backwash frequency
- Compact, rugged stainless steel construction
- Flow rate up to 18 litres/second (65 m<sup>3</sup>/hour)
- Four versions to meet all industry preferences, protocols and enclosure demands



Type C - electric



Type S - electric

		Type			
		C	S	R	P
Enclosure:	IP54	■	■	■	■
	IP65		■	■	■
	IP68			■	
	EX			■	■
Electrical Supply:	12VDC	■			
	24VDC		■	■	■*
	110VAC		■	■	■*
	240VAC		■	■	■*
	3-phase			■	
Pneumatic Supply:	6 bar				■
Maximum Pressure Rating:	10 bar	■	■	■	■
Automatic Backwash:	DP	■	■	■	■
	Time	■	■	■	■
	Manual	■	■	■	■



Type R - electric



Type P - pneumatic

Standard Micron Filtration Ratings:  
 10, 20, 25, 35, 50, 75, 100, 125, 150, 200, 400  
 \*For control circuit



**Cross Manufacturing Company (1938) Ltd**  
 Midford Road  
 Bath BA2 5RR  
 England  
 Tel: 01225 837000  
 Fax: 01225 834115  
 filters@crossmanufacturing.com  
 www.crossmanufacturing.com/filters